

**Product Data Sheet** 

D-00-L27

## **KODAK LED Flashlight Handy 50**

## Effective: 31/11/2017

OHS



Designation	KODAK LED Flashlight Handy 50*
Dimensions	L 70 x W 35 x H 20 mm
Weight	24 g ± 5 %(without battery)
Battery size Application	2 x CR2032
Operating Modes	1 <sup>st</sup> press to the on/off button- High beam. 2 <sup>nd</sup> press to the on/off button- Low beam. 3 <sup>rd</sup> press to the on/off button- Strobe.
Features	Carabiner.
LED Light	50 lumens
Weather Resisting Rating	IP44 (protected against objects having a diameter greater or equal to 1mm, protected against water sprayed from all directions ).
Compliance	RoHS Directive 2002/95/EC, EU WEEE Directive 2012/19/EU and also compliant with EU REACH requirements
Housing material	ABS + Rubber
Operating temperature	-10°C- 60°C ; 45-85% RH

\* Denotes Colour options.

The Data in this publication represents product tested under the conditions specified. They do not represent standards or specifications which must be met. Strand reserves the right to change and improve product characteristics at any time. Contents herein do not constitute a warranty.



The Kodak trademark and the Kodak trade dress are used under license from Kodak. © 2017 STRAND EUROPE LTD www.kodakbatteries.strandeurope.com

Page **1** of **1** Version: 1.0 Date: 17 March 2016