



Dimensions are in millimeters and include label.

<b>Chemical system:</b>	Nickel-Metal Hydride			
<b>Designations:</b>	IEC HR6, ANSI 1.2H2			
<b>Nominal Voltage:</b>	1.2V			
<b>Nominal Capacity:</b>	1700 mAh	2100 mAh	2500 mAh	2600 mAh
<b>Rated, Minimum Capacity:</b> (IEC/EN 61951-2)	1600 mAh	2000 mAh	2400 mAh	2500 mAh
<b>Charging Condition:</b>	170 mA for 16h	210 mA for 16h	250 mA for 16h	260 mA for 16h
<b>Maximum continuous discharge:</b>	3.2 A to 1.0V	4.0 A to 1.0 V	4.8 A to 1.0V	5.0 A s to 1.0V
<b>Maximum intermittent discharge</b>	4.8 A	6.0 A	7.2 A	7.5 A
<b>Minimum charging cycles:</b>	500	1000	300	300
<b>Average Weight:</b>	28.0 g			
<b>Recommended storage temperature:</b>	+5 – +25 °C, RH no more than 75%			
<b>Operating temperatures:</b>	0 – 50 °C			
<b>Terminals:</b>	Flat contacts			
<b>Jacket:</b>	PVC Label			

Note:

- 1) No added Mercury / 99.9999% Mercury Free
- 2) No added Lead /99.999% Lead Free
- 3) No added Cadmium / 99.9999% Cadmium Free
- 4) No added PFOS (Perfluorooctane sulfonates)
- 5) This battery complies with ANSI C18, IEC 60086, and EU Directive 2006/66/EC, 2006/122/EC
- 6) SDS sheets are available on request from Strand Europe Ltd.
- 7) Charge or Discharge at extreme high or low temperature will significantly affect service and cycle life.
- 8) For best performance after long period of non-use, charge and discharge the battery several times.

